

In order to successfully composite computer graphics elements into live action scenes it is important that the lighting of the CG object match the lighting of the scene into which it is being composited. One technique that has been used to reproduce the incident illumination in a live-action scene is to acquire a high-dynamic-range photograph of a mirrored ball placed in the scene and then use this light-probe image as a source of illumination for image-based lighting.¹

PREVIOUS WORK

Currently, in order to create a high dynamic range image of a mirrored ball one must take an iterative series of photographs with the exposure value of each image being stopped down by a given increment from the exposure value of the one before. Later, each of the images are assembled into a single high dynamic range image using a program such as HDR Shop². If an artist wished to accurately illuminate a CG object traveling through a complex lighting environment, it would be necessary to capture these iterative photographs at numerous locations (ideally at every frame) along the object's path. Clearly, this would be an ambitious task.

TECHNIQUE

One solution for creating a real-time high-dynamic range light probe is to develop a system in which multiple exposures of the same image can be captured within a single video frame. We did this by modifying a five point multi-image filter (a faceted lens that is commonly used to create photographic kaleidoscope effects), and applying successively increasing values of neutral density gel to four of the five facets of the filter (3, 6, 10 and 13 stops). This modified filter effectively produces a single image that is divided into five identical regions, with the center region capturing a "direct" view and the four outer regions stopped down to their respective exposure values. This modified filter is placed on a video camera that is mounted along with a mirrored ball on a span of angle iron (see Figure 1).

Assuming the relation between the camera and the ball never changes, the light probe only needs to be calibrated once. To compensate for the angle shift introduced by parallax effects from the facets of the multi-image filter, one can compute the arctangent of the distance between facets divided by the distance between the lens and the silver ball. By determining the number of degrees each facet is offset from the center, we are able to warp each region of the filter according to the direction space of its view of the ball. In our case, each facet's view of the ball was computed to be 2.7 degrees off from center.

More accurate calibration can be done with the help of a light stage,² which provides a "master key" for factoring out lens distortion and imperfections in the mirrored ball. However, we found that simply computing the pixel shift and then overlapping each region of the filter was sufficient for assembling a usable image.

In order to capture high dynamic range light probe data at every frame along a path, one presses "record" on the video camera and carries the light probe along the desired path. A computer program then imports each recorded frame, isolates the five distinct images

in the frame, aligns them according to predetermined calibration data, and then assembles the aligned images into a high dynamic range omnidirectional measurement of incident illumination.

RESULTS

Figure 2 shows a raw, unprocessed image from the light probe.

Figure 3 shows several exposures of a high dynamic range image that were assembled from a single light probe frame.

Figure 4 shows a CG object, lit with captured light from the real time high dynamic range light probe.

CONCLUSION

This new technique will permit artists to composite CG objects into dynamic complex lighting environments, accurately reproducing high dynamic range lighting parameters for each frame. In the future, this technique would benefit from greater precision in applying the neutral density gels to the multi-image filter, a smaller camera rig, and higher resolution video cameras.

References

1. Debevec, P. (1998). Rendering synthetic objects into real scenes: bridging traditional and image-based graphics with global illumination and high dynamic range photography. In *Proceedings SIGGRAPH 98*.
2. Debevec, P., Hawkins, T., Tchou, C., Duiker, H.P., Sarokin, W., & Sagar, M. Acquiring the reflectance field of a human face. In *Proceedings SIGGRAPH 2000*.
3. Tchou, C. & Debevec, P. (2001). HDR shop. *SIGGRAPH 2001 Conference Abstracts and Applications*.



Figure 1. A real time high dynamic range light probe.



Figure 2. Five exposures of a mirrored ball in a single image.



Figure 3. Five exposures of a high dynamic range image captured in a single frame.



Figure 4. A CG model that is synthetically illuminated with light captured with the real time light probe.